



- 400 lbs. (182 kg) Max. Vertical Load.
- 2,000 lbs. (910 kg) Max. Gross Trailer Weight.
- Formed Steel body for strength and durability.
- Supplied with a tethered lock pin.

All dimensions shown are nominal

- Steel  
- Zinc Clear Plating

14	HM121	$\phi 3/8$ " SAFETY CLIP with Chain/Cable	STEEL	1
13	MI-29	$\phi 1/8$ " x 1" LG COTTER PIN	STEEL	1
12	WA60	$\phi 3/8$ " STANDARD FLAT WASHER	STEEL	1
11	SP2000-1	SHORT SPACER	STEEL	3
10	SP2000	LONG SPACER	STEEL	1
9	HM22	$\phi 3/8$ " x 1.25" LG. CLEVIS PIN	STEEL	1
8		M12 - 1.75 x 75mm Lg Cap Screw	Gr. 8.8	1
7		M12 - 1.75 STEEL LOCKNUT	Gr. 8.8	1
6		M10 - 1.5 x 75mm Lg Cap Screw	Gr. 8.8	1
5		M10 - 1.5 STEEL LOCKNUT	Gr. 8.8	1
4	SL2000	Secondary Lock	STEEL	1
3	PL2000	Primary Lock	STEEL	1
2	TGB2000	Trailer Guide Bracket	STEEL	1
1	F17820	1 7/8" Ball, straight CLASS 1 coupler	STEEL	1
ITEM NO.	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL SPECIFICATION	QTY REQD

NAME	DATE		<b>POWER PIN INC.</b>
DRAWN	LW Sept 27/16		
DESCRIPTION:		TRAILER BALL HITCH ASSEMBLY 1 7/8" BALL x 2.0" STRAIGHT COUPLER 2,000 LBS. MGW	
PART NO.		TB17820	REV 0
www.powerpin.ca			

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POWER PIN INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POWER PIN INC. IS PROHIBITED.