



- 400 lbs. (182 kg) Max. Vertical Load.
- 2,000 lbs. (910 kg) Max. Gross Trailer Weight.
- Formed Steel body for strength and durability.
- Supplied with a tethered lock pin.

All dimensions shown are nominal

- Steel
- Zinc Clear Plating

ITEM NO.	PART OR IDENTIFYING NO.	NOMENCLATURE OR DESCRIPTION	MATERIAL SPECIFICATION	QTY REQD
14	HM121	$\phi 3/8"$ SAFETY CLIP with Chain/Cable	STEEL	1
13	MI-29	$\phi 1/8" \times 1"$ LG COTTER PIN	STEEL	1
12	WA60	$\phi 3/8"$ STANDARD FLAT WASHER	STEEL	1
11	SP2000-1	SHORT SPACER	STEEL	3
10	SP2000	LONG SPACER	STEEL	1
9	HM22	$\phi 3/8" \times 1.25"$ LG. CLEVIS PIN	STEEL	1
8		M12 - 1.75 x 70mm Lg Cap Screw	Gr. 8.8	1
7		M12 - 1.75 STEEL LOCKNUT	Gr. 8.8	1
6		M10 - 1.5 x 70mm Lg Cap Screw	Gr. 8.8	1
5		M10 - 1.5 STEEL LOCKNUT	Gr. 8.8	1
4	SL2000	Secondary Lock	STEEL	1
3	PL2000	Primary Lock	STEEL	1
2	TGB2000	Trailer Guide Bracket	STEEL	1
1	F17825	1 7/8" Ball, straight CLASS 1 coupler	STEEL	1

NAME	DATE	POWER PIN INC.
DRAWN: LW	Oct 12/16	
DESCRIPTION:		TRAILER BALL HITCH ASSEMBLY 1 7/8" BALL x 2.5" STRAIGHT COUPLER 2,000 LBS. MGTV
PART NO. TB17825		
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POWER PIN INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POWER PIN INC. IS PROHIBITED.		REV 0 www.powerpin.ca