



	CATEGORY 3					CATEGORY 4					CATEGORY 5	
	BH3SABLA	BH3SABA	BH3SABSA	BH3SAB3HA	BH3SAB3HSA	BH4SABA	BH4SABSA	BH4SAB3HA	BH4SAB3HSA	BH4SAB3HSSA	BH5SABA	BH5SABSA
A = Draw Pin Size	2"	1.5"	1.25"	1.5"	1.25"	2"	1.5"	2"	1.5"	1.25"	2.75"	2"
B = Ball Housing Diameter	5.62"	5.62"	5.62"	5.62"	5.62"	5.8"	5.8"	5.62"	5.62"	5.62"	7.25"	7.25"
C = Receiver Width	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"
D = Draw Pin to Hole Mounting	6.91"	6.91"	6.91"	6.32"	6.32"	6.92"	6.92"	7"	7"	7"	7.57"	7.57"
E = Nose to Hole Mounting	9.72"	9.72"	9.72"	9.12"	9.12"	10.07"	10.07"	9.82"	9.82"	9.82"	11.20"	11.20"
f= Ball Thickness	2.66"	2.53"	2.53"	2.53"	2.53"	2.66"	2.53"	2.66"	2.53"	2.53"	2.88"	2.75"
G = Bolt Hole Size	1"	1"	1"	.77"	.77"	1"	1"	1"	1"	1"	1"	1"
H = Bolt Hole Distance	2.25"	2.25"	2.25"	1.5"	1.5"	2.25"	2.25"	2.25"	2.25"	2.25"	2.25"	2.25"
Number of Bolts in Receiver	2	2	2	3	3	2	2	3	3	3	3	3
J = Receiver Height	4.5"	4.5"	4.5"	4.5"	4.5"	4.5"	4.5"	6.75"	6.75"	6.75"	6.75"	6.75"
K = Hole Center to Back	1.18"	1.18"	1.18"	.87"	.87"	1.18"	1.18"	1.18"	1.18"	1.18"	1.18"	1.18"
L= Tongue Thickness	1.94"	1.94"	1.94"	1.88"	1.88"	2"	2"	2.06"	2.06"	2.06"	2.38"	2.38"
Weight (lbs.)	25.5	25.5	25.5	22.8	23	27	27	31	31	31	41.8	42.8

Flanged Bushing Options

Replacment Bushings

HM34F	Flanged Bushing Cat.5	2.00" ID & 2.75" OD	HM31B	Spherical Bushing Cat. 3&4	2.00" ID
HM35F	Flanged Bushing Cat.3&4	1.50" ID & 2.00" OD	HM32B	Spherical Bushing Cat. 3&4	1.50" ID
HM37F	Flanged Bushing Cat.3&4	1.25" ID & 2.00" OD	HM33B	Spherical Bushing Cat. 5	2.75" ID
HM38F	Flanged Bushing Cat.3&4	1.25" ID & 1.50" OD	HM36B	Spherical Bushing Cat. 3	1.25" ID
			HM42B	Spherical Bushing Cat. 5	2.00" ID