



Dimensions

	Category 5		Category 4				Category 3						
	BH5SABA	BH5SABSA	BH4SABA	BH4SABROA	BH4SABSA	BH4SAB3HA	BH4SAB3HSA	BH3SABLA	BH3SABA	BH3SABSA	BH3SAB3HLA	BH3SAB3HA	BH3SAB3HSA
Receiver height A	6.75"	6.75"	4.5"	4.91"	4.5"	6.75"	6.75"	4.5"	4.5"	4.5"	4.5"	4.5"	4.5"
Bolt hole centers distance B	2.25"	2.25"	2.25"	—	2.25"	2.25"	2.25"	2.25"	2.25"	2.25"	1.5"	1.5"	1.5"
Bolt hole center to back C	1.18"	1.18"	1.18"	2.25"	1.18"	1.18"	1.18"	1.18"	1.18"	1.18"	.87"	.87"	.87"
Bolt hole size D	1"	1"	1"	1"	1"	1"	1"	1"	1"	1"	.77"	.77"	.77"
Draw pin to hole mounting E	7.57"	7.57"	6.92"	5.87"	6.92"	7"	7"	6.91"	6.91"	6.91"	6.32"	6.32"	6.32"
Nose to hole mounting F	11.20"	11.20"	10.07"	8.75"	10.07"	9.82"	9.82"	9.72"	9.72"	9.72"	9.12"	9.12"	9.12"
Ball thickness G	2.88"	2.75"	2.56"	2.56"	2.56"	2.56"	2.56"	2.56"	2.56"	2.56"	2.56"	2.56"	2.56"
Tongue thickness H	2.38"	2.38"	2"	2.06"	2"	2.06"	2.06"	1.94"	1.94"	1.94"	1.88"	1.88"	1.88"
Width for receiver I	3.96"	3.96"	3.96"	2.88"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"	3.96"
Draw pin size J	2.75"	2"	2"	2"	1.5"	2"	1.5"	2"	1.5"	1.25"	2"	1.5"	1.25"
Ball housing diameter K	7.25"	7.25"	6.3"	5.75"	6.3"	5.62"	5.62"	5.62"	5.62"	5.62"	5.62"	5.62"	5.62"
Number of bolts in receiver	3	3	2	1	2	3	3	2	2	2	3	3	3
Weight (lbs)	41.8	42.8	27	28.7	27	31	31	25.5	25.5	25.5	23	22.8	23

Articulating Ball Bushings

Up to 45° of total articulation while maximizing contact area. Reduces hitch wear, easily removable with no tools.



		Inner Diam.
Category 5	HM33B	2 3/4"
Category 5	HM42B	2"
Category 3&4	HM31B	2"
Category 3&4	HM32B	1 1/2"
Category 3	HM36B	1 1/4"

Flanged Sleeve Bushings

Fast step-down to smaller pin sizes when using AB Bushings. Flanged to ensure easy pin drop-ins.



		Inner Diam.	Outer Diam.
Category 5	HM34F	2"	2 3/4"
Category 3&4	HM35F	1 1/2"	2"
Category 3&4	HM37F	1 1/4"	2"
Category 3&4	HM38F	1 1/4"	1 1/2"